



# electric cylinder ESBF-LS-40-200-3P

Part number: 2295382

**FESTO**

With lead screw, electrically actuated spindle that converts the rotary motion of the motor into linear motion of the piston rod.



## Data sheet

Feature	Value
Size	40
Stroke	200 mm
Piston rod thread	M12x1,25
Reversing backlash	100 µm
Spindle diameter	16 mm
Spindle pitch	3 mm/U
Max. angular deflection of piston rod +/-	0.2 deg
Based on the standard	ISO 15552
Assembly position	Any
Piston-rod end	Male thread
Motor type	Stepper motor Servomotor
Position detection	For proximity sensor
Design structure	Electro-cylinder with sliding thread spindle
Spindle type	Plain thread
Protection against torque/guide	with plain-bearing guide
Max. acceleration	2.5 m/s <sup>2</sup>
Max. speed	0.15 m/s
Repetition accuracy	±0,05 mm
Duty cycle	100 %
Corrosion resistance classification CRC	2 - Moderate corrosion stress
Storage temperature	-20 ... 60 °C
Food-safe	See Supplementary material information
Relative air humidity	0 - 95 %
Protection class	IP40
Ambient temperature	0 ... 50 °C
Max. drive torque	2.4 Nm
Max. radial force at drive shaft	130 N
Max. feed force Fx	1,000 N
No-load driving torque	0.2 Nm
Reference value for working load, horizontal	100 kg
Reference value for working load, vertical	100 kg
Mass moment of inertia JH per metre of stroke	0.5075 kgcm <sup>2</sup>
Mass moment of inertia JL per kg of working load	0.0023 kgcm <sup>2</sup>
Mass moment of inertia, JO	0.0449 kgcm <sup>2</sup>
Moving mass with 0 mm stroke	317 g
Additional weight per 10 mm stroke	48 g
Basic weight for 0 mm stroke	1,079 g
Additional mass factor per 10 mm of stroke	11 g
Mounting type	with internal (female) thread or accessories
Interface code, actuator	D40
Materials note	Contains PWIS substances

Feature	Value
	Conforms to RoHS
Material cover	Wrought Aluminium alloy Smooth anodised
Material piston rod	High alloy steel, non-corrosive
Material screws	Steel Galvanised
Material spindle nut	Roller bearing steel
Material spindle	Roller bearing steel
Material cylinder barrel	Wrought Aluminium alloy Smooth anodised